



## Low Voltage Joints

### Application

Heatshrink joints is the proven technological way offering the ideal solution for the jointing of low voltage cables. Tank's Heatshrink products offers excellent insulation, sealing and protection properties in order to re-establish the cable construction and offers standard jointing kits ranging from 1.5 to 300mm<sup>2</sup>. Customised kits are available on request to suite the customer needs.

Quality assurance has always played a major role in the development of Joints. The Tank accreditation to the SABS ISO 9001 quality assurance standard, enhances the quality of our materials and the security and integrity of the system.

### Features

- Excellent electrical, thermal and mechanical performance
- Superior sealing capability
- Impact resistant
- Unlimited shelf life
- Low inventory



## TECHNICAL INFORMATION

| Cable Kit Range                         |
|---|
| 1.5mm <sup>2</sup> - 6mm <sup>2</sup>   |
| 4mm <sup>2</sup> - 10mm <sup>2</sup>    |
| 16mm <sup>2</sup> - 25mm <sup>2</sup>   |
| 35mm <sup>2</sup> - 50mm <sup>2</sup>   |
| 70mm <sup>2</sup> - 95mm <sup>2</sup>   |
| 120mm <sup>2</sup> - 150mm <sup>2</sup> |
| 185mm <sup>2</sup> - 300mm <sup>2</sup> |

